

992.4 (RVRH) Riverview Row Housing Zone

1. General Purpose

To allow for the development of street oriented Multi-unit Housing in the form of row housing that allows a greater building Height and the opportunity for development on individual shallow lots where access is from a Lane to a rear attached Garage.

2. Permitted Uses

1. Minor Home Based Business
2. Multi-unit Housing, in the form of row housing
3. Secondary Suite
4. Supportive Housing, Restricted to Limited Supportive Housing
5. Urban Gardens
6. Urban Outdoor Farms
7. Fascia On-premises Signs

3. Discretionary Uses

1. Child Care Services
2. Major Home Based Business
3. Residential Sales Centre
4. Freestanding On-premises Signs
5. Temporary On-premises Signs

4. Development Regulations

1. Site area and Site dimensions shall be in accordance with Table 1.

Table 1 Site Area and Site Dimensions			
	minimum Site Area	minimum Site Width	minimum Site Depth
i. Multi-unit Housing - Internal Dwelling	90 m ²	3.6 m	25.0 m
ii. Multi-unit Housing - End Dwelling	120 m ²	4.8 m	25.0 m
iii. Multi-unit Housing - Corner Dwelling	150 m ²	6.0 m	25.0 m

2. Each Multi-unit Housing building shall not exceed a maximum of 48 m in width.

3. The maximum Height shall not exceed 13.0 m.
4. The maximum total Site Coverage shall be in accordance with Table 2.

Table 2 Site Coverage	
i. Multi-unit Housing - Internal Dwelling	57%
ii. Multi-unit Housing - End Dwelling	45%
iii. Multi-unit Housing – Corner Dwelling	40%

5. The minimum Front Setback shall be 4.5 m.
6. The minimum Rear Setback shall be 5.5 m.
7. The minimum Side Setback shall be 1.2 m, except that it shall be 2.4 m for a Corner Lot where the Side Yard Abuts a flanking public roadway other than a Lane.
8. Vehicular access shall be from a Lane.
9. Each Dwelling unit within the Multi-unit Housing building shall be individually defined through a combination of architectural features that may include variations in the rooflines, projection or recession of the façade, porches or entrance features, building materials, or other treatments.
10. Each Multi-unit Housing building shall be limited to a maximum of 5 principal Dwelling units.
11. On Corner Sites the Façades of a principal building Abutting the Front Lot Line and the flanking Side Lot Line shall use consistent building materials and architectural features, and shall include features such as windows, doors, or porches.
12. Multi-unit Housing shall not repeat the same architectural features more than six times on a block face.
13. Signs shall comply with the regulations found in Schedule 59A.