

#### **PART B: Zone Specific Application Review Template**

#### **II. RF2- Low Density Infill Zone**

This form includes regulations which apply to Expedited Infill development permits for single-detached dwellings, with or without secondary suites, and semi-detached dwellings located within a **Low Density Infill** (**RF2**) zone.

Complete this form (Part B) and the Mature Neighbourhood Overlay and General Regulations form (Part A). Only complete the section(s) of this form that correspond with the dwelling type that you are applying for:

- a) Single Detached Dwelling ...... Page 2
- b) Secondary Suite ..... Page 4
- c) Semi-detached Dwelling ...... Page 5

Combine both Part A and Part B in **one PDF document** and submit it via eServices with your Development Permit. This is a recommended document for the Expedited Infill Review Process.



## a) Single Detached Dwelling

**Note:** Only complete this section if you are applying for a single-detached dwelling within a RF2 zone.

	Regulation					Required	Proposed	Compliant?
120.4.1 120.4.1.a	<b>Development Regulations</b> the minimum Site area shall be 250.8 m <sup>2</sup> ;							
120.4.1.b	the minimu	m Site Wid	th shall be 7	7.5 m; and				
120.1.4.c	the minimu	m Site dep	th shall be 3	80.0 m.				
120.4.6	Maximum S	i <b>ge</b> ge shall be a						
		Principal Dwelling	Accessory Building	Principal building with attached Garage	Total Site Coverage			
120.4.6.a	Site area 300 m² or greater	28%	12%	40%	40%			
120.4.6.b	Site area less than 300 m <sup>2</sup>	28%	14%	42%	42%			
120.4.7	Notwithstanding subsection 120.4(7), the maximum Site Coverage for the Principal Dwelling/building and the maximum total Site Coverage shall be increased by up to 2% of the Site Area, in addition to any increase allowed under Section 87, to accommodate single Storey Unenclosed Front Porches.							



	Regulation	Required	Proposed	Compliant?
120.4.10 120.4.10.a	Side Setbacks Side Setbacks shall total at least 20% of the Site Width, with a minimum Side Setback of 1.2 m on each side;			
120.4.10.b	on a Corner Site where the building faces the Front Lot Line, the minimum Side Setback flanking the roadway shall be 20% of the Width of the Lot flanking the roadway, to a maximum of 4.5 m;			
120.4.10.c	on a Corner Site where the building faces the flanking Side Lot Line, the minimum Side Setback abutting the flanking Side Lot Line shall be 4.5 m If the Dwelling does not have an attached Garage also facing the flanking Side Lot Line, the minimum Side Setback may be reduced to 3.0 m, in order to increase the Private Outdoor Amenity Area in the interior Side Yard; and			
120.4.13	On Corner Sites the façades of a principal building abutting the Front Lot Line and flanking Side Lot Line shall use consistent building materials and architectural features, and shall include features such as windows, doors, or porches.			
120.4.14	Except for Garden Suites and Secondary Suites, each Dwelling that has direct access to ground level shall have an entrance door or entrance feature facing a public roadway, other than a Lane. On Corner Sites, the entrance door or entrance feature may face either the Front Lot Line or the flanking Side Lot Line.			
120.4.15	A maximum of one building containing Single Detached Housing, Semi-detached Housing, or Duplex Housing per Site shall be allowed.			



# b) Secondary Suite

**Note:** Only complete this section if you are applying for a single-detached dwelling with a secondary suite within a RF2 zone.

	Regulation	Required	Proposed	Compliant?
86 86.1	Secondary Suite A Secondary Suite shall comply with the following regulations:  The maximum Floor Area of the Secondary Suite, excluding the area covered by stairways, shall be less than the Floor Area of the principal Dwelling.			
86.2	A Secondary Suite shall be developed in such a manner that the exterior of the principal Dwelling containing the Secondary Suite shall appear as a single Dwelling from a public roadway other than a Lane.			
86.3	Only one of a Secondary Suite or a Garden Suite may be developed in conjunction with each principal Dwelling, except in the RF1, RF2, and RF3 Zones where one Secondary Suite and one Garden Suite may both be developed in conjunction with a Single Detached House.			
86.4	A Secondary Suite shall not be developed within the same principal Dwelling containing a Group Home or Limited Group Home, Child Care Services or a Major Home Based Business, unless the Secondary Suite is an integral part of a Bed and Breakfast Operation in the case of a Major Home Based Business.			
86.5	A maximum of one Household shall occupy a Secondary Suite.			



## c) Semi-detached Dwelling

**Note:** Only complete this section if you are applying for a semi-detached dwelling within a RF2 zone.

	Regulation					Required	Proposed	Compliant?
120.4.3 120.4.3.a	<b>Development Regulations</b> the minimum Site area shall be 442.2 m <sup>2</sup> ;							
120.4.3.b	on a non-Corner Lot, the minimum Site Width shall be 13.4 m, except that if the Dwellings are arranged along the depth of the Site rather than the width, the minimum Site Width may be reduced to 10.0 m;							
120.4.3.c	on a Corne and	inimum Site						
120.4.3.d	the minimu	th shall be 3						
120.4.6	<b>Maximum</b> Maximum	<b>ige</b> ge shall be a						
		Principal Dwelling	Accessory Building	Principal building with attached Garage	Total Site Coverage			
120.4.6.c	Site area 600 m² or greater	28%	12%	40%	40%			
120.4.6.d	Site area less than 600 m <sup>2</sup>	28%	14%	42%	42%			



	Regulation	Required	Proposed	Compliant?
120.4.7	Notwithstanding subsection 120.4(7), the maximum Site Coverage for the Principal Dwelling/building and the maximum total Site Coverage shall be increased by up to 2% of the Site Area, in addition to any increase allowed under Section 87, to accommodate single Storey Unenclosed Front Porches.			
120.4.10 120.4.10.a	Side Setbacks Side Setbacks shall total at least 20% of the Site Width, with a minimum Side Setback of 1.2 m on each side;			
120.4.10.b	on a Corner Site where the building faces the Front Lot Line, the minimum Side Setback flanking the roadway shall be 20% of the Width of the Lot flanking the roadway, to a maximum of 4.5 m;			
120.4.10.c	on a Corner Site where the building faces the flanking Side Lot Line, the minimum Side Setback abutting the flanking Side Lot Line shall be 4.5 m If the Dwelling does not have an attached Garage also facing the flanking Side Lot Line, the minimum Side Setback may be reduced to 3.0 m, in order to increase the Private Outdoor Amenity Area in the interior Side Yard; and			
120.4.10.d	on a Corner Site where Semi-detached Housing with a Site area less than 600 m² or Single Detached Housing or Duplex Housing with a Site area less than 300 m² faces the flanking Side Lot Line, Side Setbacks shall be a minimum of 1.2 m for the interior Side Setback, and a minimum of 2.5 m for the flanking Side Setback. However, if an attached Garage faces the flanking Side Lot Line, the Side Setback from the flanking Side Lot Line to the Garage shall be a minimum of 4.5 m			
120.4.12	Each principal Dwelling within Semi-detached Housing shall be individually defined through a combination of architectural features that may include variations in the rooflines, projection or recession of the façade, porches or entrance features, building materials, or other treatments.			



	Regulation	Required	Proposed	Compliant?
120.4.13	On Corner Sites the façades of a principal building abutting the Front Lot Line and flanking Side Lot Line shall use consistent building materials and architectural features, and shall include features such as windows, doors, or porches.			
120.4.14	Except for Garden Suites and Secondary Suites, each Dwelling that has direct access to ground level shall have an entrance door or entrance feature facing a public roadway, other than a Lane. On Corner Sites, the entrance door or entrance feature may face either the Front Lot Line or the flanking Side Lot Line.			
120.4.15	A maximum of one building containing Single Detached Housing, Semi-detached Housing, or Duplex Housing per Site shall be allowed.			