



**NOTES:**

1. 1 - NON-ILLUMINATED STREET SIGN, 24" X 72", 10 lbs./ea
2. 1 - 90 deg. DOUBLE ARM STREELIGHT EXTENSION
3. 2 - 3 LIGHT 12" FIXTURE c/w 5" BORDERED BACKBOARD, 23" X 52", 35 lbs./ea
4. 2 - 4 LIGHT 12" FIXTURE c/w 5" BORDERED BACKBOARD, 23" X 64", 45 lbs./ea
5. 2 - 30" X 30" ILLUMINATED TRAFFIC SIGN, 52 lbs./ea
6. 1 SET "WALK/WAIT" FIXTURE, 18" X 18", 65lbs./ea (total incl. steel frame).
7. 1" PIPETHREAD REQUIRED ON POLE SHAFT COMPLETE WITH RUBBER COVER LOCATED AT 10'6" FROM BASE OF POLE SHAFT ON CANTILEVER ARM SIDE OF POLE SHAFT.
8. 5 - 1" RUBBER GROMMETS REQUIRED ON MAST ARM, LOCATED AT 14', 22', 30', 40', 49' FROM CENTER OF POLE.

	TRANSPORTATION SERVICES TRAFFIC OPERATIONS BRANCH
	<b>TRAFFIC SIGNALS</b>
STANDARD TRAFFIC SIGNAL CANTILEVER STRUCTURE 15.24m(50') ARM 394mm(15.5") BCD	
NOT TO SCALE	CCL - 15.24m (50')